TECHNICAL DATA SHEET



October 24, 2025

Name Natural Rubber Sheet (Pure Gum)

Code GMS-SS-O40

1. DIMENSIONS AND APPEARANCE

Thicknessin1/32 - 2Lengthft5 - 300Widthin2 - 72

Surface finishing Smooth finish, both sides

Colour Orange

2. PHYSICAL PROPERTIES

Hardness Tensile strength Elongation	Shore A psi (MPa) %	40 ± 5 2300 (15.9) 600	ASTM D2240 ASTM D412 ASTM D412
Heat resistance (70°C, 70h) Change in hardness	Shore A, max	± 15	ASTM D573/2240
Change in tensile	%, max	± 30	ASTM D573/412
Change in elongation Low working temp	%, max °F	- 50 - 40	ASTM D573/412
High working temp	°F	158	

3. TOLERANCES

TARGET THICKNESS, in (mm)	MINIMUM, mm	MAXIMUM, mm	WIDTH TOLERANCE, in
1/32 (0.8)	0.54	1.05	-0/+1
1/16 (1.6)	1.21	1.97	-0/+1
3/32 (2.4)	2.00	2.76	-0/+1
1/8 (3.2)	2.79	3.56	-0/+1
3/16 (4.8)	3.95	5.58	-0/+1
1/4 (6.4)	5.54	7.16	-0/+1
3/8 (9.5)	8.71	10.34	-0/+1
1/2 (12.7)	11.51	13.89	-0/+1
5/8 (15.9)	14.4	17.48	-0/+1
3/4 (19.1)	16.69	21.41	-0/+1
1 (25.4)	22.86	27.94	-0/+1

Whitmore Inc. cannot foresee all circumstances under which this information and our products in conjunction with other manufactures products may be used. Physical properties are typical values obtained from sample testing at Akron laboratories or GCP Approved Supplier™ laboratories. Actual production values may vary. It is the users' responsibility to ensure the products are appropriate for their application. We accept no responsibility for results obtained by the application of the information or the safety and suitability of our products, either alone or in combination with other products. If you have any questions in this regard please contact: info@whitmoreinc.com.